

**Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1-44 (**Cancelled**)

45. (**Currently Amended**) In a telecommunication system, a method for routing optical data signals using a first communication path comprising at least one optical fiber extending between at least two network elements of the telecommunication system ~~and comprising at least one optical link~~ for carrying optical data signals separated from optical addressing signals, and a second communication path comprising one or more optical fibers extending between ~~the at least two nodes~~ network elements of the telecommunication system ~~and comprising one or more optical links~~ for carrying optical addressing signals separated from said optical data signals, the method comprising the steps of providing a combination of said optical addressing signals to provide addressing information required for establishing an address for routing the optical data signals, and providing at least one of said at least one optical fiber comprised in said first communication path for carrying said optical data signals separated from said optical addressing signals ~~second communication path as one or more optical links which is physically is~~ different from any of the ~~optical links~~ one or more optical fibers comprised in said ~~first~~ second communication path, and wherein said optical data signals being conveyed separately from said optical addressing signals along said at least one optical fiber were generated at a plurality of different network elements.

46. (**Currently Amended**) In a telecommunication system, a method for routing optical data signals between at least two routers in the system, which method comprises:

generating first optical addressing signals by converting signals  
identifying a destination address into corresponding optical addressing signals;  
transmitting said optical addressing signals separated from said optical data signals over one or more optical addressing links/fibers comprised in a first communication path, said first communication path extending from one of the at least two routers to another router of the at least two routers; and

concurrently or subsequently transmitting said optical data signals separated from said optical addressing signals to said another router via said optical data link extending from said one router of the at least two routers to the another router on at least one partially physically a second communication path comprising at least one optical fiber, said second communication path extending from said one router of the at least two routers to the another router, and comprising at least one optical fiber which is different path from any of the at least one optical fibers comprised in said first communication path, wherein said optical data signals being conveyed separately from said optical addressing signals were generated at a plurality of different network elements said one or more optical addressing links extending from said one router one of the at least two routers to the another router of the at least two routerssaid.

47. (**Currently Amended**) The method according to claim 46, further comprising the steps of:

generating new optical addressing signals associated with the next section of a transmission path extending from ~~the current~~ said one router of the at least two routers towards said destination address;

transmitting the new optical addressing signals over one or more optical addressing ~~links~~ fibers extending between said ~~current one~~ router of the at least two routers and a ~~next~~ another router;

transmitting said optical data signals to said ~~next~~ another router via an optical ~~data-link~~ fiber extending between said ~~current one~~ router of the at least two routers and said ~~next~~ another router wherein said optical ~~data-link~~ fiber over which said optical data signals are transmitted is at least partially different from said one or more optical ~~addressing links~~ fibers for carrying said optical data signals separated from said optical addressing signals; and

repeating the steps of generating new optical addressing signals, transmitting the new optical addressing signals separated from said optical data signals and transmitting said optical data signals separated from said new optical addressing signals to said ~~next~~ another router, until said optical data signals are transmitted to said destination address via subsequent routers located along a transmission path extending towards said destination address.

48. **(Previously Presented)** The method according to claim 45, further comprising the step of transmitting, at one of two binary illumination states, the information extracted from at least one of the optical addressing signals.

49. **(Previously Presented)** The method according to claim 45, further comprising the steps of transmitting, at a certain illumination level, at least one of the optical addressing signals and presenting, by absence of illumination at least one other optical addressing signal.

50. **(Previously Presented)** The method according to claim 45, wherein at least two of the optical addressing signals are transmitted each at substantially the same wavelength and at a different illumination intensity and wherein each of the illumination intensities corresponds to a different addressing information.

51. **(Previously Presented)** The method according to claim 45, wherein at least two of the optical addressing signals are transmitted each at substantially the same intensity and at a different wavelength, and wherein each of the different wavelengths corresponds to a different addressing information.

52. **(Previously Presented)** The method according to claim 50, wherein an optical address is derived from a combination of at least two optical addressing signals each transmitted at a different wavelength and at a different intensity from the other.

53. **(Previously Presented)** The method according to claim 46, wherein the transmission of at least one of the optical data signals is delayed until the following steps are performed:

decoding said optical addressing signals;  
deriving addressing information from the decoded optical  
addressing signals; and  
if required, generating another, or using said, optical routing  
address for further routing of said optical data signals.

54. **(Previously Presented)** The method according to claim 53,  
wherein the transmission of said at least one of the optical data signals is delayed by  
allowing said at least one of the optical data signals to pass through an optic fiber of a  
length corresponding to a desired delay in the transmission.

55. **(Currently Amended)** ~~In a telecommunication system, a~~ The  
~~method for routing optical data signals between at least two network elements in the~~  
~~system, which method comprises~~ according to claim 46, further comprising:

~~generating first optical addressing signals by converting the signals~~  
~~identifying a destination address into corresponding optical addressing signals;~~  
~~assigning optical addressing links which extend towards said~~  
~~destination address based on said first optical addressing signals;~~  
~~establishing a data transmission path between a first network element~~  
~~which is a transmission source transmitting said optical addressing signals over one~~  
~~or more optical data links, and a second network element which is a destination for~~  
~~the transmission of the optical data signals wherein said optical data links are on at~~  
~~least one partially physically different path from said optical addressing links~~  
~~extending from the first network element to the second network element;~~

transmitting to said ~~transmission source~~ one of the at least two routers  
an indication that said optical data signals can be forwarded towards their  
destination;  
receiving said indication at said ~~transmission source~~ one of the at least  
two routers; and  
transmitting, responsive to receiving said indication, said optical data  
signals towards said ~~destination~~ another router along said data transmission path.

**56. (Cancelled)**

**57. (Currently Amended)** The method according to claim 55, ~~wherein said first optical addressing signals are transmitted along a first path and~~  
wherein at least one part of said ~~first path~~ second communication path extends in a  
network different than a network in which said optical data signals are transmitted to  
their destination.

**58. (Cancelled)**

**59. (Previously Presented)** The method according to claim 57,  
wherein said at least one part of said first path extends in a network which uses at  
least one of the following protocols: MPLS, MP $\lambda$ S, IP, ATM and SS7.

**60. - 65 (cancelled).**

66. **(Currently Amended)** Routing apparatus for routing optical data signals, said apparatus comprises:

means for generating first optical addressing signals by converting signals identifying a destination address into corresponding optical addressing signals;

means for transmitting said optical addressing signals from said routing apparatus to a second router over a ~~second~~ first communication path ~~comprising one or more optical links~~ comprising at least one optical fiber for carrying said optical addressing signals separated from said optical data signals; and

means for transmitting said optical data signals from said routing apparatus to said second router along a ~~first~~ second communication path ~~comprising at least one optical link~~ comprising at least one optical fiber, said at least one optical fiber for carrying said optical data signals separated from said optical addressing signals and wherein said ~~first communication path~~ comprises at least one optical link fiber for carrying said optical data signals separated from said optical addressing signals is which is physically different from any of the at least one optical links fibers comprised in said ~~second~~ first communication path, and wherein said optical data signals being conveyed separately from said optical addressing signals, were generated at a plurality of different network elements.

67. **(Currently Amended)** The apparatus according to claim 66, in which at least one of the optical addressing ~~signal~~ signals is transmitted at a certain illumination level and at least another optical addressing signal is presented by absence of illumination.

68. **(Previously presented)** The apparatus according to claim 66, in which at least two of the optical addressing signals are transmitted at substantially similar wavelengths and at a different illumination intensity, and each of the illumination intensities corresponds to a different addressing information.

69. **(Previously presented)** The apparatus according to claim 66, wherein at least two of the optical addressing signals are transmitted at a different wavelength, and each of the different wavelengths corresponds to a different addressing information.

70. **(Previously presented)** The apparatus according to Claim 69, wherein said at least two of the optical addressing signals are transmitted at substantially similar intensity.

71. **(Previously presented)** The apparatus according to claim 66, in which at least two of the optical addressing signals are transmitted each at a wavelength and intensity that are different from the wavelength and intensity of the other one of said at least two of the optical addressing signals.

72. **(Currently Amended)** The apparatus according to claim 66, further comprising:

means for delaying said optical data signals;

means for decoding said optical addressing ~~data~~signals;



means for deriving addressing information from the decoded optical  
addressing signals; and

means for generating optical routing address signals for further routing  
of said optical data signals.

**73. (Previously Presented)** The apparatus according to claim 72,  
comprising an optic fiber for delaying the transmission of at least one of the optical  
data signals and means for directing said at least one of the optical data signals to  
pass through said optic fiber.

**74 - 81 (cancelled).**

**82. (Currently Amended)** Apparatus for transmitting optical data  
signals between at least two network elements in a system, comprising:

a) signal generating means for generating optical addressing  
signals by converting signals identifying a destination address into corresponding  
optical addressing signals;

b) transmission means for transmitting said optical addressing  
signals separated from said optical data signals over a first communication path  
comprising over one or more optical addressing links fibers and extending between  
the at least two network elements towards said destination address; and

c) transmission means for transmitting said optical data signals  
towards said destination address along a second communication path comprising at  
least one optical fiber extending between the at least two network elements for

conveying said optical data signals separated from said optical addressing signals, wherein at least one of said at least one optical fiber in said second communication path is physically different than any of the at least one optical fibers comprised in thea second communication path for any one of said one or more optical addressing links extending between the at least two network elements, and wherein said optical data signals being conveyed separately from said optical addressing signals, were generated at a plurality of different network elements.

**83. (Previously Presented)** The apparatus according to Claim 82, further comprising means for receiving an indication that said optical data signals can be forwarded towards their destination, wherein said means for transmitting said optical data signals is adapted to transmit the optical data signals towards said destination responsive to receiving said indication.

**84. (Previously Presented)** The apparatus according to claim 83, operatively associated with at least one link that is a member of the group comprising: a link in a MPLS network, a link in a MPλS network, a link in an ATM network and a link in an SS7 network, which link is adapted to receive said indication.

**85 (cancelled).**

**86. (Currently Amended)** A telecommunication routing apparatus comprising:

- a) receiving means for receiving first optical addressing signals;
- b) signal generation means for generating second optical addressing signals associated with the next section of a transmission path extending towards a destination address;
- c) transmission means for transmitting the second optical addressing signals separated from optical data signals over one or more optical ~~addressing links~~fibers extending from a ~~first network element~~said telecommunication routing apparatus towards the destination address representing a second network element;
- d) receiving means for receiving optical data signals generated at a plurality of different network elements; and
- e) transmission means for transmitting the optical data signals received towards the destination address along an optical path extending from the ~~first network element~~ telecommunication routing apparatus toward to the second network element which comprises at least one optical ~~link~~fiber that is physically different from a ~~path extending from the first network element to the second network element~~ for any one of said one or more optical ~~addressing links~~fibers over which the second optical addressing signals separated from the optical data signals are transmitted.